

# Tempo

Design by Lieve Altherr.

## Reference

**5774.**

## Application

Hanging lamps

## Installation type

Surface

## Description

Tempo pendant lamps are a design by Lieve Altherr. Suspended from the cable, the blown glass diffuser offers subtle nuances of transparency and translucency. All models of the Tempo collection incorporate LED lighting.

## Diffuser

Blow-glass diffuser

## Materials

LED support: Aluminum

Diffuser: Blown-glass

Ceiling rose: Steel

## Finish


 **5774-18** Graphite (ADAPTA RF 9913 WX)

 **5774-35** Brick (NCS S 4040-Y70R)

 **5774-58** Cream (RAL 7044)

 **5774-62** Green (NCS S 3010-G20Y)

## Sketch



## Electrical characteristics

1 x LED 4W 350mA

Total 4.0 W



**A++**

# VIBIA



**Light source:** 2700K CRI >90 440.81 lm 110 lm/W

**Driver included:** CC - Constant Current 350 mA 110-240V 50/60Hz

**Electronic dimming** 1-10V PUSH

**ficha.fichatecnicaproducto.regulacion.opcional** DALI or Casambi

## Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0149 m<sup>3</sup> /

Gross weight 2.0 kg. / Net weight 1.4 kg.


## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

Efficiency : 55.71 lm/W

Coordinate system : CG

Total flux : 302.04 lm

Maximum value : 203.44 cd

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m

## Certificates



# Tempo

Design by Lieve Altherr.

## Reference

**5778.**

## Application

Hanging lamps

## Installation type

Surface

## Description

Tempo pendant lamps are a design by Lieve Altherr. Suspended from the cable, the blown glass diffuser offers subtle nuances of transparency and translucency. All models of the Tempo collection incorporate LED lighting.

## Diffuser

Blow-glass diffuser

## Materials


LED support: Aluminum

Diffuser: Blown-glass

Ceiling rose: Steel

## Finish


 **5778-18** Graphite (ADAPTA RF 9913 WX)

 **5778-35** Brick (NCS S 4040-Y70R)

 **5778-58** Cream (RAL 7044)

 **5778-62** Green (NCS S 3010-G20Y)

## Sketch



## Electrical characteristics

1 x LED 4W 350mA

Total 4.0 W



**A++**

# VIBIA



**Light source:** 2700K CRI >90 440.81 lm 110 lm/W

**Fixture:** 261.43 lm 65.35 lm/W

**Driver included:** CC - Constant Current 350 mA 110-240V 50/60Hz

**Electronic dimming** 1-10V PUSH

**ficha.fichatecnicaproducto.regulacion.opcional** DALI or Casambi

## Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0454 m<sup>3</sup> /

Gross weight 4.0 kg. / Net weight 2.5 kg.


## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

Efficiency : 47.27 lm/W

Coordinate system : CG

Total flux : 261.43 lm

Maximum value : 190.70 cd

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m

## Certificates



# Tempo

Design by Lieve Altherr.

## Reference

**5780.**

## Application

Hanging lamps

## Installation type

Surface

## Description

Tempo pendant lamps are a design by Lieve Altherr. Suspended from the cable, the blown glass diffuser offers subtle nuances of transparency and translucency. All models of the Tempo collection incorporate LED lighting.

## Diffuser

Blow-glass diffuser

## Materials

LED support: Aluminum

Diffuser: Blown-glass

Ceiling rose: Steel

## Finish



**5780-18** Graphite (ADAPTA RF 9913 WX)



**5780-35** Brick (NCS S 4040-Y70R)




**5780-58** Cream (RAL 7044)



**5780-62** Green (NCS S 3010-G20Y)

## Sketch



## Electrical characteristics

1 x LED 4W 350mA

Total 4.0 W



# VIBIA



**Light source:** 2700K CRI >90 440.81 lm 110 lm/W

**Fixture:** 280.99 lm 70.24 lm/W

**Driver included:** CC - Constant Current 350 mA 110-240V 50/60Hz

**Electronic dimming** 1-10V PUSH

**ficha.fichatecnicaproducto.regulacion.opcional** DALI or Casambi

## Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0336 m<sup>3</sup> /

Gross weight 4.0 kg. / Net weight 2.5 kg.


## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

## Certificates



# Tempo

Design by Lieve Altherr.

## Reference

**5776.**

## Application

Hanging lamps

## Installation type

Surface

## Description

Tempo pendant lamps are a design by Lieve Altherr. Suspended from the cable, the blown glass diffuser offers subtle nuances of transparency and translucency. All models of the Tempo collection incorporate LED lighting.

## Diffuser

Blow-glass diffuser

## Materials

LED support: Aluminum

Diffuser: Blown-glass

Ceiling rose: Steel

## Finish



**5776-18** Graphite (ADAPTA RF 9913 WX)



**5776-35** Brick (NCS S 4040-Y70R)




**5776-58** Cream (RAL 7044)



**5776-62** Green (NCS S 3010-G20Y)

## Sketch



## Electrical characteristics

1 x LED 4W 350mA

Total 4.0 W



# VIBIA



**Light source:** 2700K CRI >90 440.81 lm 110 lm/W

**Fixture:** 317.77 lm 79.44 lm/W

**Driver included:** CC - Constant Current 350 mA 110-240V 50/60Hz

**Electronic dimming** 1-10V PUSH

**ficha.fichatecnicaproducto.regulacion.opcional** DALI or Casambi

## Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.0429 m<sup>3</sup> /

Gross weight 5.5 kg. / Net weight 4.0 kg.


## Installation and assembly

Please, see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

Efficiency : 57.61 lm/W

Coordinate system : CG

Total flux : 317.77 lm

Maximum value : 315.71 cd

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m

## Certificates

