


SFR4

120VAC LED DoB 4" Ceiling Square with Optional recessed can Mounting Kits and socket Adapters

SFR6

120VAC LED DoB 6" Ceiling Square with Optional recessed can Mounting Kits and socket Adapters



Catalog #		Type
Project		Date
Prepared by		

LED



CA Title 24

[4"]



SFR4

LED
Ceiling Square
Flush Mount
Recess Can Mounting Kits

[6"]



SFR6

DESIGN FEATURES

Electrical Connection

- 120VAC LED Power Supply on-board with stated-of-the-art customized IC chip (DoB).
- 10-100% triac dimming with most of leading and trailing edge incandescent & low voltage dimmer switches.
- Advanced driver circuit design (Pat. Pending) prevents damage to the LED module and switch from common inrush currents.
- Recommended for use max. 45 fixtures per run on a 600W max load dimmer switch.
- Available in 2700K, 3000K, 3500K, 4000K color temperatures.
- Mounting on 4" J-box with 2 screws from base plate.
- Optional E26 and GU24 Adapters and Mounting Kits are available for mounting over 4" and 6" IC / Non-IC type Recessed cans from below.

Finish

- WH : White
- Contact factory for custom colors

Limited Warranty

- LED Module: 5 years/50K hours
- Product: 3 years

Listing

- cCSA-us Damp Location
- ENERGY STAR
- California Title 24

OPTIONS



Specification	SFR4	SFR6
Model #	SFR4	SFR6
Input Voltage	120VAC	120VAC
Lens Dimension	4-1/16" Square	6-7/16" Square
Housing Dimension	4-15/16"	7-5/16"
Height	1/2"	1/2"
LED Wattage	10W	15W
Lumen	630 (80CRI)	980 (80CRI)
Efficacy (LPW)	63 (3000K)	65 (3000K)
Lens	Plastic	Plastic
Description	LED DoB 4" Ceiling Square	LED DoB 6" Ceiling Square
Environment	Wet location	Wet location

Ordering Information

Model	-CRI	Color Temp.*	Finish*	-Options
SFR4 = 4", 10W DoB Ceiling Square	-8 = 80 CRI -9 = 90 CRI	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	blank = Standard White	-4MTL = SFR4 kit for 4" Recess cans -6MTL = SFR6 kit for 6" Recess cans -E26A = Med Base Adapter -GU24A = GU24 Adapter
SFR6 = 6", 15W DoB Ceiling Square				

Example : SFR6-830-6MTL-E26A

* Consult factory for other Color Temperatures and Finishes